



### 2023 Charger Specifications

| Feature                              | Model  |                    |                    |                    |
|--------------------------------------|--|--------------------|--------------------|--------------------|
|                                      | 25552KAJ-8010  | 25552KAT-8010      | 25560KAJ-8010      | 25560KAT-8010      |
| Product Name                         | Kawasaki FX801V  | Kawasaki FX801V    | Kawasaki FX801V    | Kawasaki FX801V    |
| Engine                               | Kawasaki FX801V  | Kawasaki FX801V    | Kawasaki FX801V    | Kawasaki FX801V    |
| Horsepower                           | 25.5   | 25.5               | 25.5               | 25.5               |
| Cylinders                            | 2  | 2                  | 2                  | 2                  |
| Oil Capacity                         | 2.1 qt (2 L)   | 2.1 qt (2 L)       | 2.1 qt (2 L)       | 2.1 qt (2 L)       |
| Drive System                         | Hydro-Gear ZT-4400   | Hydro-Gear ZT-4400 | Hydro-Gear ZT-4400 | Hydro-Gear ZT-4400 |
| Fuel Capacity                        | 10.25 Gallon   | 10.25 Gallon       | 10.25 Gallon       | 10.25 Gallon       |
| Steering Control                     | Joystick   | Twin Lever         | Joystick           | Twin Lever         |
| Stand-up Deck                        | Standard   | Standard           | Standard           | Standard           |
| ContourDTS™ Equipped                 | Standard   | Standard           | Standard           | Standard           |
| Roll Over Protection- Folding (ROPS) | Standard   | Standard           | Standard           | Standard           |
| Tires, Rear                          | 24x9.5-12  | 24x9.5-12          | 24x12-12           | 24x12-12           |
| Tires, Front                         | 13x6.5-6   | 13x6.5-6           | 13x6.5-6           | 13x6.5-6           |
| Turning Radius                       | Zero-Turn  | Zero-Turn          | Zero-Turn          | Zero-Turn          |
| Ground Speed (Forward/Reverse)       | 11 mph/6 mph   | 11 mph/6 mph       | 11 mph/6 mph       | 11 mph/6 mph       |
| Length                               | 83"  | 83"                | 83"                | 83"                |
| Height: top of ROPS extended         | 74"  | 74"                | 74"                | 74"                |
| Height: top of ROPS folded           | 47"  | 47"                | 47"                | 47"                |
| Width, Tractor (outside rear tires)  | 51"  | 51"                | 56"                | 56"                |
| Width, Deck w/ Chute                 | 65"  | 65"                | 73"                | 73"                |
| Width, Deck Chute Up                 | 53"  | 53"                | 61"                | 61"                |
| Cutting Width                        | 52"  | 52"                | 60"                | 60"                |
| Cutting Height                       | 1.5" - 5" (1/4" increments)  |                    |                    |                    |
| Deck Construction                    | Laminated Welded 10 Gauge Steel Deck with 10 Gauge Reinforcement and Additional 7 Gauge Spindle Mounting Reinforcement, including protective bullnose front & high impact anti-scalp rollers; 3/8" x 2" wear bar on trim edge, replaceable polymer wear strip on trim edge |                    |                    |                    |
| Blade Engagement                     | Electric Clutch, Warner  |                    |                    |                    |
| Blade Length                         | 18.375"  | 18.375"            | 21"                | 21"                |
| Spindle Assembly                     | Cast iron housing; 1.5" diameter shaft; maintenance free & field serviceable   |                    |                    |                    |
| Blade Tip Speed, approx.             | 19,000 fpm   | 19,000 fpm         | 19,000 fpm         | 19,000 fpm         |
| Weight, approx.                      | 1208 lbs   | 1216 lbs           | 1248 lbs           | 1256 lbs           |
| Seat                                 | Suspension Seat with 2-1/4" Adjustable Travel, Vibration Isolators, Adjustable Seat Back Recline, Seat Back Pocket and Adjustable Arm Rests  |                    |                    |                    |
| Other Standard Features              | Hour Meter, Electric Start, Cup Holder, Storage Tray, Front Step, Float Fuel Gauge, Trailer Hitch Receiver   |                    |                    |                    |

Due to continuous product improvement, specifications are subject to change without notice.